

FIXED LOCK TOGGLE

DWG # 125-FLT ISO REV 2
DATE 11/07

ITEM: FIXED LOCK TOGGLE

MATERIAL: TYPE 316 STAINLESS STEEL.

FITTING TYPE: NON-ADJUSTABLE CABLE END FITTING

SWAGE TYPE: MACHINE HEX SWAGE AT FACTORY (ALSO AVAILABLE IN CABLECRIMP HAND SWAGE STYLE FOR ATTACHING IN THE FIELD).

POST TYPE: TUBULAR METAL POSTS ONLY (POSTS NOT INCLUDED).


FASTENING TO POST: PASS THROUGH HOLE IN END/TERMINATION POST AND FITTING AUTOMATICALLY TOGGLES INTO LOCKING POSITION INSIDE POST.

FASTENING AT ANGLES: TOGGLE ACCOMODATES ANGLES WITHOUT DRILLING ANGLED HOLES.

CABLE TENSIONING: NON-ADJUSTABLE FIXED END.

HARDWARE PAIRINGS: USUALLY PAIRED WITH ANOTHER FIXED LOCK TOGGLE PLUS AN IN-LINE TURNBUCKLE. MUST BE USED WITH A TENSION ADJUSTMENT FITTING, DO NOT PAIR WITH ANOTHER FIXED END.

SUPPLIER: FEENEY ARCHITECTURAL PRODUCTS



FIXED LOCK TOGGLE, STAINLESS STEEL

PART#	SWAGE TYPE	CABLE SIZE	LENGTH (L)	BEFORE SWAGE DIA (SBø)	ATTACHMENT POST DRILL HOLE ø
3169	MACHINE	1/8"	1-1/2"	1/4"	5/16"
3164	CABLECRIMP	1/8"	1-1/2"	7/32"	5/16"

feeneyarchitectural
PRODUCTS

CableRail™ - Custom Assemblies
2603 Union Street
Oakland, CA 94607-2423
Ph: 800-888-2418 or 510-893-9473
Fx: 510-893-9484, www.cablerail.com