



ITEM:  
MATERIAL:  
FITTING TYPE:

SLEEKLINE SURFACE MOUNT TURNBUCKLE  
TYPE 316 STAINLESS STEEL.  
ADJUSTABLE CABLE END TURNBUCKLE FOR ATTACHING &  
TENSIONING LINES. SMOOTH, ATTRACTIVE APPEARANCE WITHOUT  
ANY EXPOSED THREADS OR SWAGE ENDS.

SWAGE TYPE:

CAN BE MACHINE SWAGED IN FACTORY BUT BEST  
SUITED FOR FIELD FABRICATION USING CABLECRIMP  
HAND SWAGE STYLE.

POST TYPE:

WOOD. METAL POSSIBLE BUT NOT RECOMMENDED.  
(POSTS NOT INCLUDED).

FASTENING TO POST:

ATTACH TO FACE OF END/TERMINATION POST OR WALL  
USING TWO SCREWS OR BOLTS.

FASTENING AT ANGLES:

TURNBUCKLE MOUNTING FLANGE PIVOTS UP TO 130 DEGREES.  
ADJUST BY TURNING TUBULAR TURNBUCKLE BODY.

CABLE TENSIONING:

USUALLY PAIRED WITH FIXED SURFACE MOUNT OR ANOTHER  
SLEEKLINE SURFACE MOUNT TURNBUCKLE. ALSO MAY USE ANY  
OTHER TENSION ADJUSTMENT FITTING OR FIXED END.

HARDWARE PAIRINGS:

SUPPLIER:

FEENEY WIRE ROPE & RIGGING  
2603 UNION STREET, OAKLAND, CA 94607  
PH: 1-800/888-2418  
FAX: 1-510/893-9484  
E-MAIL: [sales@feeneywire.com](mailto:sales@feeneywire.com)  
WEB: [www.cablerail.com](http://www.cablerail.com)

SLEEKLINE SURFACE MOUNT TURNBUCKLE, STAINLESS STEEL

PART#	MODEL#	SWAGE TYPE	CABLE SIZE	HOLE DIA (Eφ)	HOLE SPAN (H)†	FLANGE WIDTH (W)	SHAFT DIA (Sφ)	BODY LENGTH (BL)	BODY DIA (Bφ)	LENGTH CLOSED (OPEN) (L)	ATTACHMENT POST DRILL HOLE φ
3309	125-SSMTB	MACHINE	1/8"	1/4"	1-3/8"	5/8"	1/4"	4-3/4"	1/2"	5-5/8" (7-1/4")	LAG OR TAP
3310	187-SSMTB	MACHINE	3/16"	1/4"	1-3/8"	5/8"	1/4"	4-3/4"	1/2"	5-5/8" (7-1/4")	LAG OR TAP
3311	CC125-SSMTB	CABLECRIMP	1/8"	1/4"	1-3/8"	5/8"	1/4"	4-3/4"	1/2"	5-5/8" (7-1/4")	LAG OR TAP
3312	CC187-SSMTB	CABLECRIMP	3/16"	1/4"	1-3/8"	5/8"	1/4"	4-3/4"	1/2"	5-5/8" (7-1/4")	LAG OR TAP

† SINCE FLANGES ARE FORMED PIECES, ALLOW A TOLERANCE OF ±1/16" ON FLANGE HOLE SPAN DIMENSION (H).