

CORNERS: DOUBLE STEEL PIPE POST WITH
CABLES TERMINATING

DWG # STL DBL CORNER 2 CAP REV 4
DATE 11/07

NOTE: DETAIL IS TYPICAL FOR 1/8", 3/16" AND
1/4" DIAMETER STANDARD CABLERAIL™ ASSEMBLIES.

1-7/8" O.D. x 1-1/2" I.D. MIN.
EXTRA STRONG STEEL PIPE OR
OTHER TYPE AND SIZE
RECOMMENDED BY
MANUFACTURER OR ENGINEER.

DRILL HOLE THROUGH
PIPE. CONFIRM DRILL
DIAMETER WITH
MANUFACTURER.

☉ CABLE

DECK BELOW

STAINLESS STEEL
QUICK-CONNECT-SS™

END FITTINGS:
END CAP, COLORED POLYETHYLENE (STANDARD) OR ST. STL. (OPTIONAL)
3/4" O.D. NYLON FLAT WASHER

END FITTINGS:
END CAP, COLORED POLYETHYLENE (STANDARD) OR ST. STL. (OPTIONAL)
ST. STL. SNUG-GRIP™ WASHER-NUT (COVERED)
3/4" O.D. NYLON FLAT WASHER

STAINLESS STEEL
THREADED TERMINAL

DRILL HOLE
THROUGH PIPE.
CONFIRM DRILL DIAMETER
WITH MANUFACTURER.

☉ CABLE

feeneyarchitectural
PRODUCTS

CableRail™ - Standard Assemblies
2603 Union Street
Oakland, CA 94607-2423
Ph: 800-888-2418 or 510-893-9473
Fx: 510-893-9484, www.cablerail.com